

## IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered). Please AMEND claims 1-3, 5, 11 and 14-16 in accordance with the following:

Sub  
C1  
B1

1. (currently amended) A communication system, comprising:

- a computer device;
- a telecommunication terminal apparatus having individual internal assemblies;
- a switch; ~~said switch, said computer device, and said telecommunication terminal apparatus all~~ allowing connection to a public telephone network,
- a first bus system that connects said computer device to said telecommunication terminal apparatus;
- a second bus system having a smaller bandwidth than said first bus system that ~~is utilized for~~ connects the connection of individual internal assemblies of said telecommunication terminal apparatus,
- an interface that connects said telecommunication terminal apparatus to said switch;
- said telecommunication terminal apparatus having a first operating mode in which reception data received from said switch are rerouted by said telecommunication terminal apparatus to said first bus system, and are forwarded via said first bus system to ~~the said~~ said computer device;
- said computer device comprising a processor for processing the reception data received by said telecommunication terminal apparatus, and for forwarding ~~said the reception~~ said data to said telecommunication terminal apparatus via said first bus system; ~~said data being transmitted for output~~ by said telecommunication terminal apparatus;
- said first bus system forwarding ~~said transmission data~~ said data produced by said telecommunication terminal apparatus to said computer device in ~~said the~~ the first operating mode, ~~said data received by for processing in~~ said data being processed with by said processor; ~~said first bus system and~~ sending said processed transmission data to said telecommunication terminal apparatus; and

said telecommunication terminal apparatus rerouting ~~said the~~ processed transmission data ~~received~~ produced by said telecommunication terminal apparatus to said interface, for forwarding to said switch.

2. (currently amended) A communication system according to claim 1, wherein~~[[:]]~~ said processor encodes ~~said the~~ transmission data produced by said telecommunication terminal apparatus, and decodes ~~said the~~ reception data received from said switch.

3. (currently amended) A communication system according to claim 1, wherein~~[[:]]~~ said first bus system is implemented utilizing a USB bus; said second bus system is implemented utilizing an IOM-2 multiplexer; and all data of said IOM-2 multiplexer are transmitted via said first bus system.

4. (previously presented) A communication system according to claim 3, wherein said IOM-2 multiplexer comprises:

31 a CTRL channel via which said computer device controls said telecommunication terminal apparatus in said first operating mode via a CTRL channel of the IOM-2 multiplexer,;

a D\* channel, via which said computer device receives items of control information from said the telecommunication terminal apparatus; and

IC channels, via which said computer device and said telecommunication terminal apparatus exchange data.

5. (currently amended) A communication system according to claim 3, wherein said IOM-2 multiplexer comprises~~[[:]]~~ B channels, and wherein said telecommunication terminal apparatus reroutes ~~said the~~ reception and transmission data only between said interface and ~~said the~~ B channels.

6. (previously presented) A communication system according to claim 1, wherein said switch is a private branch exchange.

7. (previously presented) A communication system according to claim 6, wherein said interface is a U<sub>p0/E</sub> interface.

8. (previously presented) A communication system according to claim 6, wherein said telecommunication terminal apparatus has a second operating mode, in which it is controlled in a conventional manner by said private branch exchange, and which allows operation independent of said computer device.

9. (previously presented) A communication system according to claim 1, wherein said telecommunication terminal apparatus is a telephone.

10. (previously presented) A communication system according to claim 3, wherein:  
said computer device has a program that enables simulation of a telephone answering device;  
said transmission data represent spoken text;  
said computer device further comprises a transmission data store which enables repeated time-displaced forwarding of said spoken text to said switch via said telecommunication terminal apparatus; and  
said reception data which represent messages from callers that are sent by said switch to said computer device via said telecommunication terminal apparatus, that are intermediately stored in said computer device, and that are forwarded in a time-displaced fashion via said telecommunication terminal apparatus, as reception data.

B 1  
11. (currently amended) A communication system according to claim 1, wherein:  
said computer device further comprises a video conferencing mechanism;  
said computer device obtains said the reception data from said switch via said telecommunication terminal apparatus, divides said the reception data into image data and speech data, displays said image data on a display screen of said computer device, sends said the speech data back to said telecommunication terminal apparatus, and  
said computer device assembles transmission data from said the speech data and said image data.,  
said the speech data originating from a microphone of said ~~the~~ telecommunication terminal apparatus being transmitted to said computer device via said first bus system, and said the processed transmission data being sent to said switch via said telecommunication terminal apparatus.

12. (previously presented) A communication system according to claim 1, wherein said switch corresponds to the ISDN standard.

13. (previously presented) A communication system according to claim 3, wherein said items of control information comprise items of information produced during a pressing of particular keys of said telecommunication terminal apparatus.

14. (currently amended) A method for transmitting data in a communication system having the elements of a telecommunication terminal apparatus, a computer device, and a switch, wherein said elements are connectable to a public telephone network, comprising: the steps of

connecting said computer device to said telecommunication terminal apparatus via a first bus system;

connecting individual internal assemblies of said telecommunication terminal apparatus with a second bus system having a smaller bandwidth than said first bus system;

connecting said telecommunication terminal apparatus to said switch via an interface;

receiving reception data by said telecommunication terminal apparatus from said switch;

transmitting said the reception data by said telecommunication terminal apparatus operating in a first operating mode to said first bus system, and forwarding said the reception data via said first bus system to said computer device;

processing, by a processor of said computer device, said the reception data received by said computer device from said telecommunication terminal apparatus;

forwarding, by said computer device, to said telecommunication terminal apparatus, said processed reception data via said first bus system;

further transmitting said outputting the processed reception data by said telecommunication terminal apparatus;

producing transmission data by said telecommunication terminal apparatus;

forwarding said the transmission data by said telecommunication terminal apparatus operating in said the first operating mode to said computer device via said first bus system;

processing, by said processor of said computer device, said-the transmission data received by said computer device; and

transmitting, by said computer device, to said telecommunication terminal apparatus, said-processed transmission data via said first bus system; and transmitting, by said telecommunication terminal apparatus to said interface for forwarding to said switch.

15. (currently amended) The method according to claim 14, further comprising: the steps of

sending said-the reception data received by said switch and said-the transmission data produced by said telecommunication terminal apparatus to said computer device via said telecommunication terminal apparatus, wherein said-the reception and transmission data received by said computer device represents spoken text words;

intermediately storing said-the reception and transmission data received by said computer device in a transmission data store of said computer device, wherein said computer device further comprises a program that enables simulation of a telephone answering device, and wherein said transmission data store enables repeated time-displace forwarding of said-the reception and transmission data representing spoken text words to said switch via said telecommunication terminal apparatus; and

forwarding said-the reception and transmission data received by said computer device, by said computer device, in a time-displaced fashion via said telecommunication terminal apparatus.

16. (currently amended) The method according to claim 14, further comprising: the steps of

obtaining the reception data by said computer device from said switch via said telecommunication terminal apparatus, wherein said computer device further comprises a video conferencing mechanism;

dividing, by said computer device, said-the reception data into received image data and received speech data;

displaying, by said computer device, said-the received image data on a display screen of said computer device;

sending, by said computer device, said-the received speech data back to said telecommunication terminal apparatus;

~~assembling, by said computer device, transmission data from said speech data and said image data;~~

~~transmitting the input speech data originating from a microphone of said telecommunication terminal apparatus to said computer device via said first bus system;~~

~~assembling, by said computer device, transmission data from the input speech data and the input image data; and~~

~~transmitting said speech transmission data to said switch via said telecommunication terminal apparatus.~~

B |